

BluOcean™ Serial GPRS Modem

BluOcean™ popular range of World-class standard GSM and GPRS modems are widely used by corporations and software houses across the world. To ensure quality and speed maximization, only top quality chipset from France WAVECOM WISMO™ (World No 1 Provider of Integrated Wireless Modules) is used in the BluOcean™ modems.



wavecom®

iDA
SINGAPORE

Complies with
IDA Standards
DB103815



Technical Specification

- SIM card holder integrated
- 3V SIM Interface
- Activity Status LED Indication
- Power Output: Class4 (2W @ EGSM 900/GSM 850)
Class1 (1W @ GSM 1800/1900)
- Normal operation temperature: -20 to 55°C
- Operating Voltage : 5 to 24VDC
- Typical idle mode supply current: 5mA
- Baud rates: 300-115200 bits/s
- Compliant with ETSI GSM Phase 2 +
- Control via AT commands (GSM07.07 & 07.05)
- GPRS Coding Scheme: CS1, CS2, CS3, CS4

Design

- Serial RS232 DB9 (9pin)
- Silvery Grey Color With Metal Casing
- Weight 100g With Dimension 98x54x25mm

SMS / MMS Specification

- Text and PDU mode
- Cell broadcast
- Point to Point MO and MT

Fax Specification

- Group 3 (Class 1,2)

Supported Operating System

- Windows 2000, NT, XP, Vista, Linux

Included Accessories



Power Adaptor



Antenna



Serial Cable

Type	Frequency	Coverage	Model
Quad Band	GSM 850/900/1800/1900 MHz	Worldwide	GPRS-S-W5

World No 1 Integrated Wireless Modules Embedded - Wavecom WISMO™

Connect using power cable. Suitable for desktop pc users and controllers!